



9940

TAPE CARTRIDGE

Key benefits

Reduce costs

The 9940 tape cartridge is a low cost-per-gigabyte, high-end, half-inch storage medium. It can help you save money by minimizing tape mounts and improving automation efficiency.

Save valuable floor space

With the ability to store up to 200 gigabytes of uncompressed data, the 9940 tape cartridge helps you store more information in the same footprint.

Protect data

A ground-breaking cartridge design provides exceptional physical protection to prevent costly data loss.

Protect investments

Based on the 3480 form factor, these cartridges integrate simply and easily with your current StorageTek® automated tape systems. When you use your 9940 tape cartridges with the enhanced capacity T9940B tape drive, you can increase the value of your storage media by greater than 300 percent.

Simplify integration

System testing with StorageTek's T9940A and T9940B tape drives and StorageTek libraries can save installation labor and time.

Increase data security

VolSafe® secure media technology (write once, read many or WORM) is available for securely archiving and distributing critical data.



9940 tape cartridge

As data volumes increase, you need to find innovative ways to store more data in the same footprint. This is the need met by 9940 tape cartridges. When paired with the StorageTek® T9940B tape drive, a single 9940 tape cartridge stores up to 200 gigabytes of native data, and far more with data compression. The result? You can meet your growing data storage requirements — and unleash the value of your tape drives and libraries.

Capacity-centric technology

The 9940 tape cartridge was designed so that when it is used with T9940B tape drives it can store up to 200 gigabytes of uncompressed data, or up to 400 gigabytes with 2:1 data compression, on a single cartridge. This ultra-high capacity makes the 9940 cartridge ideal for your high-volume archiving, backup and disaster recovery applications.

Easy integration

Based on the 3480 form factor, the capacity-centric 9940 tape cartridge integrates simply and easily with your current StorageTek automated tape systems. These cartridges are system-tested for use with T9940A and T9940B tape drives, as well as with supported tape automation systems and software from StorageTek.

Durable design

The 9940 tape cartridge, built to perform a minimum of 10,000 tape mounts, features a single-reel form factor with a leader block designed for high reliability. Its innovative heavy-duty shell design offers excellent physical protection, which means fewer damaged cartridges and lower replacement and data recovery costs.

Ready to use

You can save resources by having VOLSER (volume serial number) labels applied prior to delivery. 9940 tape cartridges can be pre-labeled and initialized, then verified with a triple quality check. This process reduces the pitfalls associated with poorly applied labels.

Applications

Backup and restore

Using 9940 cartridges with T9940 tape drives for backup and restore shortens backup and recovery times with high transfer rates and fewer cartridge mounts and dismounts. 9940 tape cartridges preserve data through the most strenuous reading, writing and retention processes.

Archiving

Pairing StorageTek 9940 tape cartridges with T9940 tape drives provides a high-capacity choice for enterprise archiving systems requiring continuous use and long data retention periods. When implemented with Volsafe® secure media technology, the T9940 tape drives help secure critical data as it is archived.

Disaster recovery

StorageTek's 9940 cartridges have exceptional durability and longevity. With T9940 tape drives, the 9940 tape cartridges are ideal for enterprise disaster recovery processes that remotely vault data in tape form.

9940 tape cartridge specifications

Performance

Tape speed	
Read and write	2.0 m/sec (79 ips) — T9940A 2.4 m/sec (95 ips) — T9940B
Search and rewind	11.0 m/sec (440 ips)
Formulation	Advanced metal particle (AMP)
Coercivity	1625+/-75 Oersteds (130+/-16.0 KA/m)
Substrate	Polyethylene naphthalate (PEN)
Track-following servo	Factory pre-recorded

Capacity

Capacity, native (uncompressed)	60 GB (T9940A) 200 GB (T9940B)
---------------------------------	-----------------------------------

Availability

Archival life	15–30 years
Short-length durability	80,000 read/write passes minimum
Long-length durability	6,500 read/write passes minimum
Uncorrected bit error rate	1x10 ⁻¹⁸
Permanent errors	0
Loads/unloads	10,000 minimum

Compatibility

Supported tape drives	T9940A, T9940B
Number of tracks	288 (T9940A), 576 (T9940B)
Form factor	Half-inch, 3480/3490E

Options

VolSafe® technology

The 9940 tape cartridge with VolSafe® secure media technology provides up to 200 gigabytes (native) of non-erasable, non-rewritable storage when it is used with T9940B tape drives. You retain the ability to recall that data within seconds.

Engage the storage experts

StorageTek provides world-class service and support with a full range of offerings tailored to meet your business needs. Covering over 50 countries, more than 1,900 service professionals deliver solutions that support more than 17,000 customer data centers worldwide. StorageTek Services offerings help you maintain availability, service your customers, manage growth, reduce your management burden and maximize your return on investment. To find out more about Professional Services offerings and other StorageTek solutions, contact your StorageTek representative or visit www.storageitek.com.

To learn more

To learn more about StorageTek's media cartridge technology and how it can help you unleash trapped profits in your storage environment, talk to your StorageTek representative or visit www.storageitek.com.

Mechanical

Height	1.0 in (2.54 cm)
Depth	4.92 in (12.50 cm)
Width	4.29 in (10.90 cm)
Weight	9.17 oz (262.0 g)
Drop strength	39.4 in (1.0 m)

Environmental

Relative humidity	
Operating	20%–80%
Storage up to four weeks	5%–80%
Storage — archive	30%–40%
Shipping	5%–80%
Temperature (non-condensing)	
Operating	+60° to +90° F (+15° to +32° C)
Storage up to four weeks	+40° to +90° F (+5° to +32° C)
Storage — archive	+59° to +77° F (+15° to +25° C)
Shipping	-10° to +120° F (-23° to +49° C)
Wet bulb maximum	
Operating	+78° F (+26° C)
Storage up to four weeks	+78° F (+26° C)
Storage — archive	+78° F (+26° C)
Shipping	+78° F (+26° C)

ABOUT STORAGE TEK®

Storage Technology Corporation (NYSE: STK) is a \$2 billion global company that enables businesses, through its information lifecycle management strategy, to align the cost of storage with the value of information. The company's innovative storage solutions manage the complexity and growth of information, lower costs, improve efficiency and protect investments. For more information, visit www.storageitek.com, or call 1.800.275.4785 or 01.303.673.2800.

WORLD HEADQUARTERS

Storage Technology Corporation
One StorageTek Drive
Louisville, Colorado 80028 USA
1.800.877.9220 or 01.303.673.5151

